

Complete Listing of the Claims:

No amendments to the claims are submitted herein.

Listing of Claims:

1. (Withdrawn) A method, comprising:
activating, in response to a request for a resource, at least one of a plurality of
wireless communication connections; and
transmitting a request for portions of the resource from the at least one
activated wireless communication connection.
2. (Withdrawn) The method of claim 1, further comprising:
terminating the user request for a resource; and
generating at least one corresponding request for a resource.
3. (Withdrawn) The method of claim 1, further comprising:
terminating the user request for a resource; and
generating a plurality of corresponding requests for a resource, wherein each of
the corresponding requests comprises the same source address or a different source
address.

Response After Final
Application Number: 10/695,928
Attorney Docket Number: 304931.01

4. (Withdrawn) The method of claim 1, further comprising:

transmitting the resource from a local cache to the user if the resource resides in the local cache.
5. (Withdrawn) The method of claim 1, further comprising dividing the request into a plurality of sub-requests if portions of the resource exceeds a predetermined size threshold.
6. (Withdrawn) The method of claim 1, wherein activating at least one of a plurality of wireless communication connections comprises:

determining a characteristic of a wireless communication connection; and

activating the wireless communication connection based on the characteristic.

7. (Withdrawn) The method of claim 1, wherein activating at least one of a plurality of wireless communication connections comprises:
- determining a characteristic of a wireless communication connection; and
- activating the wireless communication connection based on the characteristic,
- wherein the characteristic is selected from the group of characteristics consisting of: signal-to-noise ratio, available bandwidth, congestion, signal strength, connection cost, and bit error rate.
8. (Withdrawn) The method of claim 1, further comprising collating received portions of the resource and making the resource available to the user.
9. (Withdrawn) A computer-readable medium having computer-executable instructions for performing the method recited in claim 1.

10. (Previously Presented) A method for retrieving a resource from a remote computer using a plurality of wireless network interfaces, comprising:
- receiving, from a computing device, a request for the resource, wherein the resource comprises a plurality of objects;
 - terminating the received request;
 - determining a number of available wireless network interfaces;
 - determining a number of objects in the resource and the size of each object;
 - assigning each object to at least one available wireless network interface, at least one object in the resource being assigned a different available wireless network interface than another object in the same resource; and
 - transmitting a request for the resource, wherein the request specifies the available wireless network interface assigned to an object.
11. (Original) The method of claim 10, wherein receiving a request for the resource comprises receiving a request from a computing device over a local communication network.

12. (Original) The method of claim 10, wherein determining a number of available wireless network interfaces comprises monitoring one or more characteristics of a wireless network interface.

13. (Original) The method of claim 10, wherein determining a number of available wireless network interfaces comprises monitoring one or more characteristics of a wireless network interface, wherein the signal characteristic is selected from the group of signal characteristics consisting of: signal-to-noise ratio, available bandwidth, congestion, signal strength, connection cost, and bit error rate.

14. (Original) The method of claim 10, wherein determining a number of available wireless network interfaces comprises monitoring one or more characteristics of a wireless network interface stored in a data table in memory.

15. (Original) The method of claim 10, wherein determining a number of available wireless network interfaces comprises querying the wireless interfaces.

16. (Original) The method of claim 10, wherein determining a number of objects in the resource and the size of each object comprises querying the remote computer.

17. (Previously Presented) The method of claim 10, wherein assigning each object to at least one available wireless network interface comprises assigning an object to two or more available wireless network interfaces if the size of the object exceeds a threshold.

18. (Previously Presented) The method of claim 10, wherein assigning each object to at least one available wireless network interface comprises assigning an object to two or more available wireless network interfaces if the size of the object exceeds a threshold, wherein the threshold is a function of the bandwidth of available wireless network interfaces.

19. (Previously Presented) The method of claim 10, wherein assigning each object to at least one available wireless network interface comprises assigning an object to two or more available wireless network interfaces if the size of the object exceeds a threshold, wherein the threshold is a function of the size of an object relative to the size of other objects in the resource.

20. (Original) The method of claim 10, further comprising:

receiving objects over the plurality of assigned wireless network interfaces; and

collating the received objects to construct the resource.

21. (Original) The method of claim 10, further comprising:

transmitting the resource to the computing device that originated the request.

22. (Original) A computer-readable medium having computer-executable

instructions for performing the method recited in claim 10.

23. (Previously Presented) An apparatus, comprising:

at least one local communication network interface for receiving a request for a resource, wherein the resource comprises a plurality of objects;

a plurality of wireless network interfaces for transmitting resource requests over wireless communication connections;

a memory module; and

a processor executing logic instructions that configure the processor to:

terminate the received request;

determine a number of available wireless network interfaces;

determine a number of objects in the resource and the size of each object; and

assign each object to at least one available wireless network interface, at least one object in the resource being assigned a different available wireless network interface than another object in the same resource.

24. (Original) The apparatus of claim 23, wherein the at least one local communication network interface comprises a wireless network interface.

25. (Original) The apparatus of claim 23, wherein the plurality of wireless network interfaces comprises a first network interface for a first wireless network service provider and a second wireless network interface for a second wireless network service provider.

26. (Original) The apparatus of claim 23, wherein the processor polls the wireless network interfaces to determine characteristics of the communication connections managed by the wireless network interfaces.

27. (Original) The apparatus of claim 23, wherein the processor polls the wireless network interfaces on a periodic basis to determine characteristics of the communication connections managed by the wireless network interfaces.

28. (Original) The apparatus of claim 23, wherein the processor polls the wireless network interfaces in response to a received request to determine characteristics of the communication connections managed by the wireless network interfaces.

29. (Original) The apparatus of claim 23, wherein the processor assigns objects to wireless network interfaces according to an algorithm that maximizes bandwidth.

30. (Original) The apparatus of claim 23, wherein the processor assigns multiple wireless network interfaces to objects that exceed a size threshold.

31. (Original) The apparatus of claim 23, wherein the processor assigns multiple wireless network interfaces to objects that exceed a size threshold that is a function of the available bandwidth on one or more wireless network interfaces.

32. (Original) The apparatus of claim 23, wherein the processor assigns multiple wireless network interfaces to objects that exceed a size threshold that is a function of the size of an object relative to other objects in a resource.
33. (Original) The apparatus of claim 23, wherein the processor is further configured to receive requested resources transmitted across a plurality of wireless interfaces.
34. (Original) The apparatus of claim 23, wherein the processor is further configured to receive requested resources transmitted across a plurality of wireless interfaces, and to store received resources in the memory module.
35. (Original) The apparatus of claim 23, wherein the processor is further configured to receive requested resources transmitted across a plurality of wireless interfaces, to store received resources in the memory module, and to transmit received resources over the local communication network interface.